

Payment Automation Manager (PAM)  
Input File Specifications – Standard Payment Request

Version 5.0.0  
March 25, 2016

## Table of Contents

Table of Contents .....	2
Update Summary: .....	4
1 Input File Specification – Standard Payment Request.....	1
1.1 General Instructions .....	1
1.2 General Structure of File .....	1
1.3 File Structure Validations.....	3
1.4 Hexadecimal Character Validation .....	3
1.5 Validation for Balancing .....	4
1.6 Derived Data Elements.....	4
1.7 Input Management (IM) Interface Information.....	4
1.8 Specification Notes .....	5
2 File Record Specifications .....	6
2.1 File Header Record.....	6
2.2 ACH Schedule Header Record.....	7
2.3 Check Schedule Header Record .....	9
2.4 ACH Payment Data Record .....	11
2.5 Check Payment Data Record.....	19
2.6 ACH Addendum Record .....	27
2.6.1 CTX Validation Rules.....	28
2.6.2 ACH Addendum Record for CTX payments.....	29
2.7 CARS TAS/BETC Record .....	30
2.8 Check Stub Record.....	33
2.9 Procurement Record.....	34
2.10 DNP Record.....	35
2.11 Schedule Trailer Control Record.....	36
2.12 File Trailer Control Record .....	37
3 Appendices.....	39
3.1 Appendix A - ACH Transaction Codes.....	39
3.2 Appendix B – Agency Specific Values.....	40
3.2.1 For Custom Agency Rule ID = “IRS” and Depositor Account Number NOT equal “BONDS” .....	40
3.2.2 For Custom Agency Rule ID = “IRS” and Depositor Account Number = “BONDS” .....	42
3.2.3 For Custom Agency Rule ID = “VA” or “VACP” and Check payments...	43
3.2.4 For Custom Agency Rule ID = “VA” or “VACP” and ACH payments.....	44
3.2.5 For Custom Agency Rule ID = “SSA” and “SSA-Daily” .....	45
3.2.6 For Custom Agency Rule ID = “SSA-A” .....	46
3.2.7 For Custom Agency Rule ID = “SSA”, “SSA-A”, and “SSA-Daily” .....	46
3.2.8 For Custom Agency Rule ID = “RRB” .....	47
3.2.9 For Custom Agency Rule ID = “CCC” .....	49
3.2.10 Generic Reconciliation Field.....	49
3.3 Appendix C - Addressing Reference Information.....	50

3.4	Appendix D - Glossary of Terms .....	53
3.5	Appendix E - PaymentTypeCode Values.....	58

## Update Summary:

Section	Section/Record Name	Update:
1.5	Validation for Balancing	Added rule for allowed Transaction Codes when dollar amount is greater than zero and SEC = CTX.
2.2	ACH Schedule Header Record	<ul style="list-style-type: none"> <li>Updated validation rules for schedule number when same combination of schedule number + ALC + fiscal year) is submitted for a removed scheduled.</li> </ul> <u>Validation Clarifications:</u> <ul style="list-style-type: none"> <li>Schedule Number: Added “all” in the event Schedule number is less than 14 characters</li> <li>Payment Type Code: Added “all” clarification when payment type is less than 25 characters</li> </ul>
2.3	Check Schedule Header	<u>Validation Clarifications:</u> <ul style="list-style-type: none"> <li>Schedule Number: Added “all” in the event Schedule number is less than 14 characters</li> <li>Payment Type Code: Added “all” clarification when payment type is less than 25 characters</li> </ul>
2.4	ACH Payment Data Record	<ul style="list-style-type: none"> <li>Renamed fields to align with SRF field naming</li> <li>Added Sub Payment Type Code, Payee Address Lines 3&amp;4, Country Name, Consular Code, and Payer Mechanism</li> </ul> <u>Validation Clarifications:</u> <ul style="list-style-type: none"> <li>Amount: Updated Validation rules to reference Section 1.5 Validation for Balancing for all amount cross validations.</li> </ul>
2.5	Check Payment Data Record	<ul style="list-style-type: none"> <li>Renamed fields to align with Standard Reporting Format field naming.</li> <li>Added Sub Payment Type Code and Payer Mechanism.</li> <li>Special Handling field: Added rule to store ‘name only’ value when the schedule is marked name only and the special handling field is blank.</li> </ul>
Appendix B	Agency Specific Values	<ul style="list-style-type: none"> <li>Updated reconciliation field layout for VA and VACP check payments by adding the VA Name Code field. VA is looking for this field on their cancellation file layouts from PACER.</li> </ul>

Section	Section/Record Name	Update:
		<ul style="list-style-type: none"><li>Added “SSA-Daily” value to account for new custom agency rule id created</li></ul>
Appendix D	Glossary of Terms	Added new field definitions

## 1 Input File Specification – Standard Payment Request

This document describes the standard format, data elements, validations and agency specific information that agencies must use to submit payment requests to the Treasury Bureau of Fiscal Service Payment Automation Manager (PAM).

The Standard PAM Payment Request Format (SPR) is intended for agencies to submit one file with one or more schedules. It is not intended to allow for more than one file per schedule (i.e., one file can have multiple schedules but one schedule cannot span across multiple files.) In addition, one SPS summary certification should be submitted for each schedule in the file. One certification cannot cover multiple schedules.

When a SPR is received by Treasury, its schedules are matched to a certification from SPS based on the schedule number, ALC, amount and item count. When preparing your SPR, be mindful of these matching criteria.

Each field in the format has validation rules and indicates whether a violation results in a file, schedule or payment rejection. It should be noted that, until further notice, any schedule rejection will result in a file rejection. In the future, Treasury will pursue offering a configuration by agency to allow schedule or file resubmission.

### 1.1 General Instructions

The development version of the Standard Payment Request may differ from the version published to agencies. The current published version is noted in the validation rules for the Standard Payment Request Version field.

Agencies should:

- Ensure content of ACH files is in alignment with NACHA rules.
- Follow IAT rules for potential international payments.
- Comply with OFAC (Office of Foreign Assets Control) policies.
- Ensure payee data is correct so the transaction is payable (routing numbers, account numbers, mailing address, etc.).
- Comply with CARS reporting rules for TAS/BETC.

### 1.2 General Structure of File

Each Record on the File shall be a length of 850 positions. The Records must indicate an appropriate record code (“RC”) and be structured as indicated below. Records associated to the Check Payment Data Record and the ACH Payment Data Record can be received in any order (i.e. Addenda, CARS, Stub, Procurement). All records for one payment must be together in the file.

- **File Header Record** RC=H (There can only be one file header record)

- **ACH** Schedule Header Record RC=01(one - many Schedule Header Records in a file)
- ACH Payment Data Record RC=02 (one - many ACH Payment Data Records in a schedule)
  - ACH Addendum Record RC=03
    - none – one for each CCD or PPD Payment Data Record;
    - none – two for each IAT Payment Data Record
  - Or
  - ACH Addendum Record RC=04
    - one-999 for each CTX Payment Data Record
  - CARS TAS/BETC Record RC=G (none-many for each ACH Payment Data Record)
  - Procurement Record RC=P (none- many for each ACH Payment Data Record)
  - DNP Record RC=DD (none- one for each ACH Payment Data Record)
- **ACH** Schedule Trailer Control Record RC=T (one for each Schedule Header Record)
- **Check** Schedule Header Record RC=11 (one - many Schedule Header Records in a file)
- Check Payment Data Record RC=12 (one - many Check Payment Data Records in a schedule)
  - Check Stub Record RC=13 (none unless CheckEnclosureCode = stub, then one for each Check Payment Data Record)
  - CARS TAS/BETC Record RC=G (none - many for each Check Payment Data Record)
  - Procurement Record RC=P (none - many for each Check Payment Data Record)
  - DNP Record RC=DD (none- one for each Check Payment Data Record)
- **Check** Schedule Trailer Control Record RC=T (one for each Schedule Header Record)

- **File Trailer Control Record RC=E** (There can only be one File Trailer Control Record)

### 1.3 File Structure Validations

The file structure must follow these rules:

Rule	Result
A schedule can contain only one type of payment	If not, reject the file
If any schedule on a file is rejected, the entire file will be rejected.	File rejection
ACH Payment Data Records must be received in Routing Number order within the schedule.	If not, reject the file
Check Payment Data Records can be received in any order.	
Records associated to the Check Payment Data and ACH Payment Data Records can be received in any order (i.e. Addenda, CARS, Stub, Procurement).	
All records for one payment must have the same information in the payment identifier fields.	If not, reject the file

Field types are as follows:

- A=alphabetic; A-Z, a-z, blanks, and special characters as noted below.
- N=numeric; 0-9.
- All dollar amount fields are numeric.
- AN= alphanumeric; A-Z, a-z, 0-9, blanks, and special characters as noted below.

Space	!	"	#	\$	%	&	'	(	)	*	+	,	-	.	/
0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
`	{		}	~											

**Table 1:** Allowed Characters

### 1.4 Hexadecimal Character Validation

Rule	Result
Any data elements being validated and/or stored in PAM must be valid HEX characters.	If not, reject the file



- File formats must meet the following validation:
  - For alphanumeric and alphabetic fields, valid special characters are defined as all Hexadecimal characters with values greater than HEX “3F” (as shown in Table 1).
  - Invalid Hexadecimal characters are defined as HEX values “00” through “3F”.

### ***1.5 Validation for Balancing***

<b>Rule</b>	<b>Result</b>
If the ACH_Transaction Code indicates “Prenote” all of the payments in the schedule must be zero dollar amounts.	If not, reject the file.
If zero dollar payment amounts are received in a schedule, the ACH Transaction Code must indicate “Prenote” or the SEC code = CTX.	If not, reject the file
If greater than zero dollar payment amounts are received in the schedule, the ACH Transaction Code must <b>not</b> indicate “Zero Dollar Credit” when SEC code = CTX.	If not, reject the file.
The ScheduleTrailer.ScheduleCount must equal the accumulated number of Payments in the schedule.	If not, reject the schedule
The ScheduleTrailer.ScheduleAmount must equal the accumulated amount of Payments in the schedule.	If not, reject the schedule
The FileTrailer.TotalCount_Records must equal the accumulated number of records on the file (this includes header and trailer records).	If not, reject the file
The FileTrailer.TotalCount_Payments must equal the accumulated number of payments on the file.	If not, reject the file
The FileTrailer.TotalAmount_Payments must equal the accumulated amount of payments on the file.	If not, reject the file

### ***1.6 Derived Data Elements***

<b>Data Element</b>	<b>Derived From</b>	<b>Associated With</b>	<b>Associated Values</b>
Method of Payment	Type of data records received	Schedule	ACH, Check
Object Line 3	Enclosure Code	Check Payment Data Record	If Enclosure Code = “stub” then Object Line 3 = “Per Enclosed Mailing Notice”

### ***1.7 Input Management (IM) Interface Information***

Note: This section is subject to change in support of transitioning away from IM.

Path	Value	Notes
Original Filename	FROXX.Agency.SPR.Unique Unique=Specified by the agency to make the dataset unique for the day.	Dataset name including delimiters is up to 44 characters long. Each node can contain up to 8 characters. If the same dataset name is used within a day, the previous dataset will be overwritten.
ControlNumber	Cnnnnnn	Assigned by IM

### **1.8 Specification Notes**

- Field #s are purely for referential and discussion purposes; they are not part of the file's data.
- A “filler” or “blank” field is not validated.
- If PAM performs validations on a field, the validation rules are provided in the “Validation rules” column.
- If there is no validation rule (“n/a”), the field can contain any value including blanks
- Numeric fields that are not validated will be stored as zeros if blanks are received.
- Fields with dollar amounts do not have decimal points; the last two digits are the cents value. For example 1234567890 = \$12,345,678.90.
- Unless otherwise specified in the validation rules column, numeric fields are right justified, with zero (0) pad on the left; alpha and alphanumeric fields are left justified, with blank pad on the right.
- When left/right justification rules are listed in the validation rules column, PAM shall correct the field justification if needed. Unless otherwise specified, currency values are not formatted as zoned decimal.

## 2 File Record Specifications

### 2.1 File Header Record

File Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	Record Code	AN	"Hb"	2	1	2	If invalid, missing or out of order, reject the file	File Header Record Identifier = "H" followed by a space
2.	InputSystem	AN		40	3	42	This should match the Agency Identifier in the PAM Agency Profile. If not, reject the file.	Used to identify the sending entity (agency or automated system)
3.	Standard Payment Request Version Number	AN		3	43	45	If invalid or missing, reject the file <b>Current published version: 500</b>	Identifies the version of the Payment Request format used to prepare the PRF, e.g. 500
4.	Filler			805	46	850	n/a	

## 2.2 ACH Schedule Header Record

ACH Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
5.	Record Code	AN	"01"	2	1	2	If invalid, missing or out of order, reject the file	ACH Schedule Header Record Identifier = "01"
6.	AgencyACHText	AN		4	3	6	n/a	Used to identify the payment to the recipient. (In FedACH file Company Name field.)
7.	ScheduleNumber	AN		14	7	20	Right justify zero fill to the left and remove all spaces. If schedule number is a duplicate of 1) other schedules on this file, or 2) other schedules in PAM during a fiscal year for the ALC and the schedule's processing status is not removed, reject the schedule. If all blank or invalid, reject the schedule. Valid characters include A-Z, 0-9, dash (-).	
8.	PaymentTypeCode	AN		25	21	45	If all blank or Type of Payment not configured in PAM, reject the	See <a href="#">Appendix E</a> for a complete listing.

ACH Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
							schedule.	
9.	StandardEntryClassCode	A	CCD; PPD; IAT; CTX	3	46	48	If blank or invalid, reject the schedule.	
10.	AgencyLocationCode	N		8	49	56	Must be a valid agency location code. If not, reject the schedule.	
11.	Filler			1	57	57	n/a	
12.	Federal Employer Identification	AN		10	58	67	n/a	Position 1-9 is used as the FEIN. Position 10 is used by Treasury and

ACH Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	on Number							should remain blank. This is passed in the Company Identification field FedACH file for child support purposes. It is the FEIN of the agency that is the employer of the payee, If this is not available then provides the FEIN of the agency sending the payment.
13.	Filler			783	68	850	n/a	

### 2.3 Check Schedule Header Record

Check Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
14.	Record Code	AN	"11"	2	1	2	If invalid, missing or out of order, reject the file	Check Schedule Header Record Identifier = "11"

Check Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
15.	Schedule Number	AN		14	3	16	Right justify zero fill to the left and remove all spaces. If schedule number is a duplicate of 1) other schedules on this file, or 2) other schedules in PAM during a fiscal year for the ALC and the schedule's processing status is not removed, reject the schedule. If schedule number is all blank or invalid, reject the schedule. Valid characters include A-Z, 0-9, dash (-).	
16.	PaymentTypeCode	AN		25	17	41	If all blank or Type of Payment not configured in PAM, reject the schedule.	See <a href="#">Appendix E</a> for a complete listing.
17.	AgencyLocationCode	N		8	42	49	Must be a valid agency location code. If not, reject the schedule.	
18.	Filler	AN		9	50	58	n/a	Filler
19.	CheckPay	A	"nameonl	10	59	68	If invalid reject the	If stub, the stub record

Check Schedule Header Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	mentEnclosureCode		y” “letter”, “stub” “insert” or blank				schedule. If “stub” and there is no stub record for each payment, reject the schedule.	should be provided for each payment in the schedule using the Check Stub Record. If letter, a separate letter file should be provided.
20.	Filler			782	69	850	n/a	

## 2.4 ACH Payment Data Record

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
21.	Record Code	AN	“02”	2	1	2	If invalid, missing or out of order, reject the file	ACH Payment Record Indicator = “02”.



ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
22.	AgencyAccountIdentifier	AN		16	3	18	Can be less than 16 characters.	<p>This is the payee account number used by the agency if different from TIN. TIN must be provided in the Payee Identifier field. See field below.</p> <p>If Custom Agency Rule ID = 'VACP', do not justify, store value as received.</p> <p>This field is passed to PACER/PPS and FedACH as the Payee Account Number.</p> <p>It is displayed as the Payee ID in PACER/PPS and TCIS.</p>
23.	Amount	N	\$\$\$\$\$\$ \$cc	10	19	28	Right justify, zero fill. If invalid or all blank, mark payment as invalid See Section 1.5 Validation for Balancing for Amount, SEC, and Transaction Code cross	

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
							validation rules.	
24.	AgencyPaymentTypeCode	AN		1	29	29	n/a	
25.	IsTOP_Ofset	AN	"0";"1"	1	30	30	n/a	"0" = no "1" = yes If blank default to "1". Agreed upon between TOP and agency.
26.	PayeeName	AN		35	31	65	Left justify, blank fill. If all blank, mark payment as invalid.	This will be truncated to 22 characters when sent to FedACH for PPD and CCD. It will be truncated to 16 for CTX and 35 for IAT.
27.	PayeeAddressLine_1	AN		35	66	100	If IAT and this is all blank, mark payment as invalid	If IAT, this is required. This is designated as the payee street address for IAT payments. While not required for other entry class codes,

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								address data is requested from agencies so Treasury can send offset letters if necessary.
28.	PayeeAddressLine_2	AN		35	101	135	n/a	Optional address line.
29.	CityName	AN		27	136	162	Left justify, blank fill. If IAT and this is all blank, mark payment as invalid	Foreign city if IAT. Will be truncated to 23 characters when sent to FedACH. Optional for domestic payments (entry class codes other than IAT).
30.	StateName	AN		10	163	172	n/a	If IAT, the foreign state, territory or province name is provided in this field, if applicable.
31.	StateCodeText	AN		2	173	174	n/a	Optional field for domestic state abbreviation for PPD/CCD entries.
32.	PostalCode	AN		5	175	179	n/a	Foreign postal code (IAT) or domestic zip code (all other entry class codes).
33.	PostalCode	AN		5	180	184	n/a	Remainder of foreign

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	eExtension							postal code (IAT) or domestic 4-digit zip (all other entry class codes).
34.	CountryCodeText	AN		2	185	186	If IAT and value is blank and/or contains zeros, mark payment as invalid.	If IAT the ISO country code is required.  See the PAM website for a complete list of country codes at <a href="https://www.fiscal.treasury.gov/fsservices/gov/pmt/pam/formats.htm">https://www.fiscal.treasury.gov/fsservices/gov/pmt/pam/formats.htm</a>
35.	Routing Number	N		9	187	195	If not valid RTN, mark payment as invalid.	
36.	Account Number	AN		17	196	212	If all blank or if value contains only zeroes, mark payment as invalid.	

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
37.	ACH_TransactionCode	N		2	213	214	If 1) not one of the values listed 2) Codes 42, 43, 52, or 53 are used for a type of payment other than Vendor or 3) all blank, mark payment as invalid.	See <a href="#">Appendix A</a> for values / definitions / stored values
38.	PayeeIdentifier_Additional	AN		9	215	223	If not 9 numeric or all blank, mark payment as invalid. Blank is the only non-numeric allowed	Used to provide TOP with additional information.
39.	PayeeName_Additional	AN		35	224	258	n/a	Used to provide TOP with additional information.

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
40.	PaymentID	AN		20	259	278	If all blank or duplicate within the schedule, reject the schedule.	Unique payment identifier within the schedule for associating all related records for the payment.
41.	Reconcilement	AN		100	279	378	Store value as received, do not justify	Limited Use. Requires agency / Treasury collaboration prior to use.  See <a href="#">Appendix B</a> for Agency Specific Values.
42.	TIN	AN		9	379	387	If not 9 numeric or all blank, mark payment as invalid. Blank is the only non-numeric allowed	This is the payee TIN. This field is associated with Payee Name
43.	Payment Recipient TIN indicator	AN	"1"=SSN "2"=EIN or blank	1	388	388	If not 1, 2, or blank, mark payment as invalid. Blank is the only non-numeric allowed	Indicates the payee TIN type.

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
44.	Additional Payee TIN Indicator	AN	"1"=SSN "2"=EIN or blank	1	389	389	If not 1, 2, or blank, mark payment as invalid. Blank is the only non-numeric allowed	Indicates the type of payee identifier provided in field PayeeIdentifier_Additional.
45.	Amount eligible for offset	AN		10	390	399	If not all blank or all numeric, mark payment as invalid. Blank is the only non-numeric allowed.	The amount of the payment that is eligible for offset. Will be sent to TOP. If the entire payment is eligible for offset, pass blanks in this field. If a portion of the payment is eligible for offset, specify the amount in this field.
46.	PayeeAddressLine_3	AN		35	400	434	n/a	Optional address line.
47.	PayeeAddressLine_4	AN		35	435	469	n/a	Optional address line.
48.	CountryName	AN		40	470	509	n/a	Full name of country for foreign addresses
49.	ConsularCode	AN		3	510	512	n/a	See the PAM website for a complete list of

ACH Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								consular / geo codes at <a href="https://www.fiscal.treasury.gov/fsservices/gov/pmt/pam/formats.htm">https://www.fiscal.treasury.gov/fsservices/gov/pmt/pam/formats.htm</a> .
50.	SubPaymentTypeCode	AN		32	513	544	n/a	
51.	PayerMechanism	AN	CreditCard, DebitCard, SVC, ACH, BookEntry, EBT, or blank	20	545	564	If not one of the values listed, mark invalid.	
52.	Filler			286	565	850	n/a	

## 2.5 Check Payment Data Record

For additional clarifications for populating address fields, refer to [Appendix C](#).

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
53.	Record Code	AN	"12"	2	1	2	If invalid, missing or out of order, reject the file	Check Payment Data Record Indicator = "12"
54.	AgencyAc	AN		16	3	18	Can be less than 16	This is the payee account



Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	countIdentifier						characters.	<p>number used by the agency if different from TIN. TIN must be provided in the Payee Identifier field. See field below.</p> <p>If Custom Agency Rule ID = 'VACP', do not justify, store value as received.</p> <p>This field is passed to PACER/PPS as the Payee Account Number and displayed as the Payee ID in PACER/PPS and TCIS.</p>
55.	Amount	N	\$\$\$\$\$\$ \$cc	10	19	28	Right justify, zero fill. If invalid or all blank, mark payment as invalid.	

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
56.	AgencyPaymentTypeCode	AN		1	29	29	n/a	
57.	IsTOP_Offset	AN	"0";"1"	1	30	30	n/a	"0" = no "1" = yes If blank default to "1.
58.	PayeeName	AN		35	31	65	Left Justify, blank fill. If all blank, mark payment as invalid	
59.	PayeeAddressLine_1	AN		35	66	100	If blank and enclosure code is not "nameonly", mark payment as suspect.	Suspect indicates an internal Treasury review for mail ability; it is not marked invalid.
60.	PayeeAddressLine_2	AN		35	101	135	n/a	
61.	PayeeAdd	AN		35	136	170	n/a	

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	ressLine_3							
62.	PayeeAddressLine_4	AN		35	171	205	n/a	.
63.	CityName	AN		27	206	232		Will be truncated to 20 characters for foreign addresses when State Name is used.
64.	StateName	AN		10	233	242	n/a	Use for foreign state, province or territory name
65.	StateCodeText	AN		2	243	244		Use this field for domestic state code.
66.	PostalCode	AN		5	245	249	If domestic, blank, and enclosure code is not "nameonly" mark payment as suspect.	If foreign address, use this field for universal postal code.  If domestic, use 5 digit zip code.  Suspect indicates an internal Treasury review for mail ability; it is not marked invalid.

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
67.	PostalCodeExtension	AN		5	250	254	n/a	If foreign address, use this field for remainder of universal postal code  If domestic, use 4 digit zip code.
68.	PostNet Barcoded Delivery Point	AN		3	255	257	n/a	Includes barcode check digit
69.	Filler	AN		14	258	271	n/a	
70.	CountryName	AN		40	272	311	n/a	Full name of country for foreign addresses
71.	ConsularCode	AN		3	312	314	n/a	See the PAM website for a complete list of consular / geo codes at <a href="https://www.fiscal.treasury.gov/fs-services/gov/pmt/pam/formats.htm">https://www.fiscal.treasury.gov/fs-services/gov/pmt/pam/formats.htm</a>
72.	CheckLegendText1	AN		55	315	369	n/a	Agency provided information that will be printed at the bottom of the check and provided to PACER for cancellation notices. This can include allotter information, month/year payment is

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								for, specific note to the payee, etc.
73.	CheckLeg endText2	AN		55	370	424	n/a	Agency provided information that will be printed at the bottom of the check and provided to PACER for cancellation notices. This can include allotter information, month/year payment is for, specific note to the payee, etc.
74.	PayeeIdentifier_Additional	AN		9	425	433	If not 9 numeric or all blank, mark payment as invalid. Blank is the only non-numeric allowed.	Used to provide TOP with additional information.
75.	PayeeName_Additional	AN		35	434	468	n/a	Used to provide TOP with additional information.
76.	PaymentID	AN		20	469	488	If all blank or duplicate within the schedule, reject the schedule.	Unique payment identifier within the schedule for associating all related records for the payment. Also used to match letters to checks during printing / enclosing if check

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								enclosure code in schedule header = "letter".
77.	Reconcile ment	AN		100	489	588	Store value as received, do not justify	Limited Use. Requires agency / Treasury collaboration prior to use.  See <a href="#">Appendix B</a> for Agency Specific Values.
78.	SpecialHandling	AN		50	589	638	n/a	If CheckPaymentEnclosure Code= 'nameonly' and this field is blank, store 'name only' in this field.  Requires agency / Treasury collaboration prior to use. Used for manual handling of checks.

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
79.	TIN	AN		9	639	647	If not 9 numeric or all blank, mark payment as invalid. Blank is the only non-numeric allowed.	This is the payee TIN. This field is associated with Payee Name.
80.	USPSIntel ligentMail Barcode	AN		50	648	697		Agencies that use Intelligent Mail Barcode services from the post office must work with Treasury to get specific formatting of this field.
81.	Payment Recipient TIN indicator	AN	“1”=SSN “2”=EIN or blank	1	698	698	If not 1, 2, or blank, mark payment as invalid. Blank is the only non-numeric allowed.	Indicates the payee TIN type.
82.	Additional Payee TIN Indicator	AN	“1”=SSN “2”=EIN or blank	1	699	699	If not 1, 2, or blank, mark payment as invalid. Blank is the only non-numeric allowed.	Indicates the type of payee identifier provided in field PayeeIdentifier_Additional.
83.	Amount eligible for offset	AN		10	700	709	If not all blank or all numeric, mark payment as invalid. Blank is the only non-numeric	The amount of the payment that is eligible for offset. Will be sent to TOP.

Check Payment Data Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
							allowed.	If the entire payment is eligible for offset, pass blanks in this field. If a portion of the payment is eligible for offset, specify the amount in this field.
84.	SubPaymentTypeCode	AN		32	710	741	n/a	
85.	PayerMechanism	AN	Cash, Check, BookEntry, or blank	20	742	761	If not one of the values listed or blank, mark invalid	
86.	Filler			89	762	850	n/a	

## 2.6 ACH Addendum Record

This record is optional for PPD, CCD, and IAT Standard Entry Class Codes.



If the SEC code is “PPD” or “CCD” only one addenda is allowed per payment.

If the SEC code is “IAT” up to two remittance addenda are allowed per payment. Additionally, for IAT payments, PAM will build the Mandatory IAT Addenda Records using data provided in the Payment Data record and append this remittance addenda if provided by the agency.

ACH Addendum Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
87.	Record Code	AN	“03”	2	1	2	If invalid, missing or out of order, reject the file	ACH Addendum Record = “03”
88.	PaymentID	AN		20	3	22	If this information is not the same as in the ACH payment data record, reject the schedule.	
89.	Addenda Information	AN		80	23	102	n/a	
90.	Filler			748	103	850	n/a	

### 2.6.1 CTX Validation Rules

The validation rules in the table below apply for Standard Entry Class Code “CTX”.

Rule	Result
If the SEC code is “CTX” and the ISA, BPR, or SE segments are missing then mark payment invalid.	Mark payment invalid
If the first ACH Addendum Record in position 23-25 does not contain “ISA” then mark payment	Mark payment invalid

Rule	Result
invalid.	
For the ISA segment, the character in position 26 must equal the segment delimiter; the character in position 128 must equal the segment terminator. If the segment delimiter equals the segment terminator then mark the payment invalid.	Mark payment invalid
For the BPR segment, if BPR-02 is non-numeric then mark the payment invalid	Mark payment invalid
For the SE segment, if SE-01 is non-numeric then mark the payment invalid	Mark payment invalid
Invalid hex cannot be used for delimiters (as defined in Section 1.3)	

### 2.6.2 ACH Addendum Record for CTX payments

Use the following format for Standard Entry Class Code “CTX”.

For CTX, 999 ACH Addendum records with 10 Addenda are allowed.

Refer to PAM Website for Addenda Supplements: [https://www.fiscal.treasury.gov/fsservices/gov/pmt/ctx/ctx\\_home.htm](https://www.fiscal.treasury.gov/fsservices/gov/pmt/ctx/ctx_home.htm)

ACH Addendum Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
87.	Record Code	AN	“04”	2	1	2	If invalid, missing or out of order, reject the file	
88.	PaymentID	AN		20	3	22	If this information is not the same as in the ACH payment data record, reject the schedule.	

ACH Addendum Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
89.	Addenda Information	AN		800	23	822	See above for validation rules	Place up to ten 80 character Addenda. Position 4 of the ISA segment will be used as the data element separator and position 106 will be used as the segment terminator.
90.	Filler			28	823	850	n/a	

## 2.7 CARS TAS/BETC Record

This record is optional. However, if TAS/BETC data received in the SPS certification does not match TAS/BETC data received with the schedule, the differences will be reported to CARS. Zero to 100 TAS/BETC recommended per payment ; maximum 1000 unique TAS/BETC recommended per schedule.

CARS TAS/BETC Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
91.	Record Code	AN	"Gb"	2	1	2	If invalid, missing or out of order, reject the file	CARS TAS/BETC Record = "G" followed by space
92.	PaymentID	AN		20	3	22	If this information is not the same as the payment data record, reject the schedule.	

<b>CARS TAS/BETC Record</b>								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
93.	Sub-levelPrefixCode	AN		2	23	24	n/a	
94.	Allocation Transfer Agency Identifier	AN		3	25	27	n/a	
95.	Agency Identifier	AN		3	28	30	n/a	
96.	Beginning Period Of Availability	AN		4	31	34	n/a	
97.	Ending Period Of Availability	AN		4	35	38	n/a	
98.	Availability Type Code	AN		1	39	39	n/a	

<b>CARS TAS/BETC Record</b>								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
99.	MainAccountCode	AN		4	40	43	n/a	
100.	Sub-accountCode	AN		3	44	46	n/a	
101.	BusinessEventTypeCode	AN		8	47	54	n/a	
102.	AccountClassificationAmount	N		10	55	64	If not numeric default to zero.	
103.	IsCredit	AN	“0” or “1”	1	65	65	If blank, default to “0”	Used to indicate whether amount is a debit “0” or credit “1”.
104.	Filler			785	66	850	n/a	

## 2.8 Check Stub Record

This record is only required if the CheckEnclosureCode field in the payment data record is “stub”. Agencies must have approval from Treasury before using this service.

Check Stub Record							
#	Field Name	Type	Field Value	Length	Position	Validation rules	Notes
105.	Record Code	AN	“13”	2	1-2	If CheckEnclosureCode = “stub” and this record is missing or out of order, reject the file. If value is invalid, reject the file.	Check Stub record code = “13”
106.	PaymentID	AN		20	3-22	If this information is not the same as the payment data record, reject the schedule.	
107.	PaymentIdentificationLine_1 (through 14)	AN		55	23-77 78-132 133-187 188-242 243-297 298-352 353-407 408-462 463-517 518-572 573-627 628-682 683-737 738-792	n/a	Checks are mailed to the address in the payment data record, not the stub address.
108.	Filler			58	793-850	n/a	

## 2.9 Procurement Record

This record is optional. The recommended limit is 100 procurement records per payment.

Procurement Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
109.	Record Code	AN	"P"	2	1	2	If invalid, missing or out of order, reject the file  "P" record is only stored for Vendor Types of Payments. If record is received with any other payment type do not store the values.	Procurement record code = "P" followed by a space
110.	PaymentID	AN		20	3	22	If this information is not the same as the payment data record, reject the schedule.	
111.	ProcurementInstrumentIdentifier	AN		50	23	72	n/a	
112.	ProcurementAgencyIdentifier	AN		4	73	76	n/a	

Procurement Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
113.	IndefiniteDeliveryVehicleProcurementInstrument Identifier	AN		50	77	126	n/a	
114.	IndefiniteDeliveryVehicleAgencyIdentifier	AN		4	127	130	n/a	
115.	Amount	N		20	131	150		
116.	Filler			700	151	850	n/a	

### 2.10 DNP Record

This record is optional. Agencies must work with DNP to determine exact values to send in DNP Detail field.

DNP Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
117.	Record Code	AN	“DD”	2	1	2	If invalid, missing or out of order, reject the file	



DNP Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
118.	Payment ID	AN		20	3	22	If this information is not the same as the payment data record, reject the schedule.	
119.	DNP Detail	AN		766	23	788	Store value as received, do not justify	
120.	Filler			62	789	850	N/A	

## 2.11 Schedule Trailer Control Record

Schedule Trailer Control Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
121.	Record Code	AN	"T"	2	1	2	If invalid, missing or out of order, reject the file	Schedule Trailer Record = "T" followed by space
122.	Filler	AN	Blanks	10	3	12	n/a	
123.	Schedule Count	N		8	13	20	If invalid, reject the schedule.	See Section 1.5 Validation for Balancing for additional rules.
124.	Filler	AN	Blanks	3	21	23	n/a	
125.	Schedule Amount	N		15	24	38	If invalid, reject the schedule.	See Section 1.5 Validation for

Schedule Trailer Control Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								Balancing for additional rules.
126.	Filler			812	39	850	n/a	

## 2.12 File Trailer Control Record

File Trailer Control Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
127.	Record Code	AN	“E␣”	2	1	2	If invalid, missing or out of order, reject the file	File Trailer Record = “E” followed by a space
128.	TotalCount_Records	N		18	3	20	If invalid, reject the file	Includes header and trailer records See Section 1.5 Validation for Balancing for additional rules.
129.	TotalCount_Payments	N		18	21	38	If invalid, reject the file.	See Section 1.5 Validation for Balancing for additional rules.

File Trailer Control Record								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
130.	TotalAmount_Payments	N		18	39	56	If invalid, reject the file.	See Section 1.5 Validation for Balancing for additional rules.
131.	Filler			794	57	850	n/a	

### 3 Appendices

#### 3.1 Appendix A - ACH Transaction Codes

The following table defines the Transaction Code values received in an ACH Detail Payment record and the value PAM should record.

Transaction Code	Definition	Account Type (for recording in PAM)
22	Checking Account Credit	C
23	Checking Account Credit Prenote	C
24	Checking Account Zero Dollar Credit With Remittance	C
32	Savings Account Credit	S
33	Savings Account Credit Prenote	S
34	Savings Account Zero Dollar Credit With Remittance	S
42	General Ledger Credit	G
43	General Ledger Credit Prenote	G
52	Loan Account Credit	L
53	Loan Account Credit Prenote	L

For Custom Agency Rule ID = “IRS” and Depositor Account Number = “BONDS”:

Transaction Code	Definition	Account Type (for recording in PAM)	Savings Bonds Owner Type
22	Checking Account Credit	C	Gift
32	Savings Account Credit	S	Self

### 3.2 Appendix B – Agency Specific Values

This appendix includes derivation, parsing and storage rules for those agencies configured with a Custom Agency Rule ID in the RAT configuration. These rules are used to parse and store the reconciliation field in position 279-378 in the ACH Data Record and position 489-588 in the Check Data Record, and to derive the values for specific data elements as noted below. If the Custom Agency Rule ID has a value the following rules apply.

#### 3.2.1 For Custom Agency Rule ID = “IRS” and Depositor Account Number NOT equal “BONDS”

IRS Tax Refunds Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1	Tax Period (Year)	AN		4	1	4	n/a	
2	Tax Period (Month)	AN		2	5	6	n/a	
3	Master File Tax (MFT) Code	AN		2	7	8	n/a	
4	Service Center Code	AN		2	9	10	n/a	
5	District Office Code	AN		2	11	12	n/a	
6	File TIN Code	AN		1	13	13	n/a	
7	Name Control	AN		4	14	17	n/a	
8	Plan Report Number	AN		3	18	20	n/a	
9	Split Refund Code	AN		1	21	21		
10	Injured Spouse Code	AN		1	22	22	n/a	
11	Debt Bypass	AN		1	23	23	n/a	If there is a value in

IRS Tax Refunds Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	Indicator Code							this field, store this value instead of the value received in the payment data record.
12	Document Locator Number	AN		14	24	37	n/a	
13	Check Detail Enclosure Code	A	“enclose” or blank	10	38	47	If the field value is NOT “enclose” or blank, or Payment is ACH make the field value blank.	
14	Filler			53	48	100		

### Payment Legacy Account Symbol Derivation Rules for IRS

The following table describes the derivation of the Legacy Account Symbol value based on listed fields in the IRS Reconciliation Record. The Legacy Account Symbol value is a concatenation (with no delimiter) of the values in the following fields in the respective order of the table below.

Record the derived value in the Check Payment Detail’s Legacy Account Symbol attribute.

IRS Tax Refunds Reconciliation Field	Field Length
District Office Code	2
File TIN Code	1
Master File Tax (MFT) Code	2
Tax Period (Year)	2 (use the last two digits of the Tax Period (Year) field, which is a length of 4)

Tax Period (Month)	2
Name Control	4
Plan Report Number	3
Sample Legacy Account Symbol value: 650300912RODR123	

### 3.2.2 For Custom Agency Rule ID = "IRS" and Depositor Account Number = "BONDS"

IRS Savings Bonds Orders Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1	Tax Period (Year)	AN		4	1	4	n/a	
2	Tax Period (Month)	AN		2	5	6	n/a	
3	Master File Tax (MFT) Code	AN		2	7	8	n/a	
4	Service Center Code	AN		2	9	10	n/a	
5	District Office Code	AN		2	11	12	n/a	
6	File TIN Code	AN		1	13	13	n/a	
7	Name Control	AN		4	14	17	n/a	
8	Plan Report Number	AN		3	18	20	n/a	
9	Split Refund Code	AN		1	21	21		
10	Injured Spouse Code	AN		1	22	22	n/a	
11	Debt Bypass Indicator Code	AN		1	23	23	n/a	If there is a value in this field, store this value instead of the value received in the payment data

IRS Savings Bonds Orders Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
								record.
12	Bond Name 1	AN		33	24	56	n/a	
13	Bond REG Code	AN	"0", "1", Blank	1	57	57	n/a	Bond REG Code Indicator Values: <ul style="list-style-type: none"> <li>• 0 = Co-Owner</li> <li>• 1 = POD</li> </ul> <b>BLANK</b> = No second name owner (this is the connector)
14	Bond Name 2	AN		33	58	90		
15	Filler	AN		10	91	100		

### 3.2.3 For Custom Agency Rule ID = "VA" or "VACP" and Check payments

VA Education, C&P, and Insurance Check Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	VA Stn Code	AN		2	1	2	n/a	
2.	VA Fin Code	AN		2	3	4	n/a	
3.	VA Courtesy Code	AN		1	5	5	n/a	
4.	VA Approp Code	AN		1	6	6	n/a	
5.	VA Address Seq	AN		1	7	7	n/a	



VA Education, C&P, and Insurance Check Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
	Code							
6.	VA Policy Pre Code	AN		2	8	9	n/a	
7.	VA Policy Num	AN		2	10	11	n/a	
8.	VA Pay Period Info	AN		12	12	23	n/a	
9.	VA Name Code	AN		3	24	26	n/a	
10.	Filler			74	27	100		

### 3.2.4 For Custom Agency Rule ID = "VA" or "VACP" and ACH payments

VA Education, C&P, and Insurance ACH Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	VA Stn Code	AN		2	1	2	n/a	
2.	VA Fin Code	AN		2	3	4	n/a	
3.	VA Approp Code	AN		1	5	5	n/a	
4.	VA Address Seq Code	AN		1	6	6	n/a	
5.	VA Policy Pre Code	AN		2	7	8	n/a	
6.	VA Policy Num	AN		2	9	10	n/a	
7.	VA Pay Period Info	AN		12	11	22	n/a	
8.	Filler			78	23	100		

### 3.2.5 For Custom Agency Rule ID = "SSA" and "SSA-Daily"

SSA Daily and Monthly Benefit Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	Program Service Center Code (PSC)	AN		1	1	1	n/a	<b>Refer to the "Payment ALC Derivation Rules" section below.</b>
2.	Payment ID Code (PIC)	AN		2	2	3	n/a	
3.	TIN Indicator Offset	AN		1	4	4	n/a	If there is a value in this field, store this value instead of the value received in the payment data record..
4.	Filler			96	5	100		

### 3.2.6 For Custom Agency Rule ID = "SSA-A"

SSA Allotments Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	Program Service Center Code (PSC)	AN		1	1	1	n/a	<b>Refer to the "Payment ALC Derivation Rules" section below.</b>
2.	Payment ID Code (PIC)	AN		2	2	3	n/a	
3.	Filler			97	4	100		

### 3.2.7 For Custom Agency Rule ID = "SSA", "SSA-A", and "SSA-Daily"

For the above two reconciliation records, the following describe derivation rules for payment detail attribute values.

#### 3.2.7.1 Payment ALC Derivation Rules

The following table lists the Payment ALC for various Program Service Center (PSC) values in a Reconciliation Record. If the SSA PSC Code is not 1-8 or A-H, then use the Schedule's ALC as the Payment ALC. Record the derived value in the Payment Detail's ALC attribute [whether ACH or Check payment].

The Gray Shaded area is information only, and does not impact deriving the ALC.

<b>RSI Code PSC</b>	<b>DI Code PSC</b>	<b>Payment Agency Location Code (ALC)</b>	<b>PSC</b>	<b>All Certifications except Cycle 2, 3 and 4</b>	<b>Payment Aftermath</b>
1	A	28045200	North Eastern PSC 1		X
2	B	28045300	Mid-Atlantic PSC 2	X	X
3	C	28045400	South Eastern PSC 3		X
4	D	28045500	Great Lakes PSC 4		X
5	E	28045900	Western PSC 5	X	X
6	F	28045600	Mid-America PSC 6	X	X
7 or 8	G or H	28043000	ODO/OIO PSC 7/8	X	X
--	--	28040004	SSI	X	X

### 3.2.7.2 Payment Legacy Account Symbol Derivation Rules

The following table lists the Legacy Account Symbol value for various Program Service Center values in a Reconciliation Record. Record the derived value in the Check Payment Detail's Legacy Account Symbol attribute.

<b>Program Service Center Code</b>	<b>Legacy Account Symbol</b>
1 – 8	2828X8006000
A - H	2828X8007000

### 3.2.8 For Custom Agency Rule ID = “RRB”

RRB Daily and Monthly Benefit Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	Beneficiary Symbol	AN		2	1	2	n/a	
2.	Prefix Code	AN		1	3	3	n/a	
3.	Payee Code	AN		1	4	4	n/a	
4.	Object Code	AN		1	5	5	n/a	
5.	Filler			95	6	100		

### 3.2.9 For Custom Agency Rule ID = "CCC"

CCC Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	TOP Payment Agency ID	A		2	1	2	If one payment within a schedule contains this value, the entire schedule will be sent to TOP with this value.	
2.	TOP Agency Site ID	A		2	3	4	If one payment within a schedule contains this value, the entire schedule will be sent to TOP with this value.	
3.	Filler	AN		96	5	100		

### 3.2.10 Generic Reconciliation Field

Format should be used by agencies that need to pass the Legacy Treasury Account Symbol field to TCIS and do not have an existing reconciliation field layout. PAM will record the value received for both ACH and Check payments.

Generic Reconciliation Field								
#	Field Name	Type	Field Value	Length	Start Position	End Position	Validation rules	Notes
1.	LegacyTreasuryAccountSymbol	AN		16	1	16		
2.	Filler	AN		84	17	100		

### ***3.3 Appendix C - Addressing Reference Information***

The following information describes how address fields should be populated for check payments in order to ensure correct addressing and timely delivery to the USPS.

#### **Domestic Addresses**

Standard:

- Agency populates City Name, State Code Text, Postal Code and/or Postal Code Extension fields separately

Workaround 1:

- Agency populates Postal Code and/or Postal Code Extension fields separately, but cannot populate City Name and State Code Text fields separately

Workaround 2:

- Agency cannot populate City Name, State Code Text, or Postal Code and/or Postal Code Extension fields separately. Note: Check Detail Records with blank Postal Codes are marked suspect, requiring manual processing. This could delay delivery.

Field	Standard	Workaround 1	Workaround 2
Payee Name	✓	✓	✓
Address Line 1	✓	✓	✓
Address Line 2	✓	✓	✓
Address Line 3	✓	✓	✓
Address Line 4	✓	✓	✓
City Name	✓		
State Name			
State Code Text	✓		
Postal Code &Postal Code Extension	✓	✓	
Barcode			
Filler			
Country Name			
Consular Code			

### **Foreign Addresses**

Payment is considered foreign when Country Name, Geo Code, or Postal Code (formatted as **bbnnn**) is populated.

Standard:

- Agency populates City Name, State Name, Postal Code and/or Postal Code Extension, Country Name, and Consular Code fields separately

Workaround 1:

- Agency populates Country Name and Consular Code fields separately but cannot populate City Name, State Name, Postal Code and/or Postal Code Extension fields separately

Workaround 2:

- Agency cannot populate City Name, State Name, Postal Code and/or Postal Code Extension, Country Name, and Consular Code fields separately. Note: payments that are considered domestic will be marked suspect when Postal Code field is blank, requiring manual processing. This could delay delivery.

Workaround 3:

- Postal Code is assumed to be a Consular Code when **bbnnn** format is used

Note: Check Detail Records with Country Name or Consular Code fields populated are mailed according to foreign mailing rules. Consular Code can be populated in Consular Code or Postal Code fields.

Field	Standard	Workaround 1	Workaround 2	Workaround 3
Payee Name	✓	✓	✓	✓
Address Line1	✓	✓	✓	✓
Address Line 2	✓	✓	✓	✓
Address Line 3	✓	✓	✓	✓
Address Line 4		✓	✓	✓
City Name	✓			
State Name	✓			
State Code Text				
Postal Code & Postal Code Extension	✓			✓ ( <b>bbnnn</b> )
Barcode				



Filler				
Country Name	✓	✓		
Consular Code	✓	✓		

### 3.4 Appendix D - Glossary of Terms

Field Name	Definition
ACH_TransactionCode	Designates a transaction's account type (checking, savings, or general ledger) and the transaction type (credit, or prenote).
AccountNumber	The payment recipient's bank account number.
AccountClassificationAmount	The transaction amount associated with TAS/BETC to be reported to Treasury for the Central Accounting Reporting System (CARS) compliancy.
Addenda Information	Additional information about the payment to be included in ACH addenda (PPD+ and CCD+)
AgencyAccountIdentifier	Account number used internally by an agency to identify a payee.
AgencyIdentifier	Used in conjunction with the main account code, represents the department, agency, or establishment of the U.S. government that is responsible for the TAS.
AgencyLocationCode	Identifies the accounting office within an agency that reports disbursements and collections to Treasury.
AgencyPaymentTypeCode	Internal agency code used to identify the type of payment within the specific agency.
AgencyACHText	Used to identify the agency responsible for the payments. First four bytes go to FedACH.
AllocationTransferAgencyIdentifier	Represents the agency receiving funds through an allocation transfer.
Amount	The amount of the transaction.
Amount eligible for offset	Indicates the amount of the payment that is eligible for offset. This is sent to TOP for offsetting purposes.
AvailabilityTypeCode	Identifies no-year accounts (X), clearing/suspense accounts (F), Treasury central summary general ledger accounts (A), and merged-surplus accounts (M).
BeginningPeriodOfAvailability	In annual and multiyear accounts, identifies the first year of availability under law that an account may incur new obligations.
BusinessEventTypeCode	Identifies the type of activity (gross disbursement, offsetting collection, investment in Treasury securities, etc.) and the effect of a transaction on the Fund Balance With Treasury (FBWT). Is used in combination with the Treasury Account Symbol to classify transactions reported to Treasury through all Government-wide

Field Name	Definition
	Accounting (CARS-compliant) Financial Management Systems.
CheckPaymentEnclosureCode	Code denoting that a check will include an enclosure – either a stub or a letter.
CheckLegendText1	Free-form field for agency's use – all data in this field is printed on the check.
CheckLegendText2	Free-form field for agency's use – all data in this field is printed on the check.
CityName	Name of the city in which the payee resides.
ConsularCode	Indicates the code for mailing bulk check shipments to foreign countries.
CountryCodeText	The ISO country code for the country in which the payment recipient resides. Used for IAT payments.
CountryName	The full name of the country in which the payment recipient resides.
EndingPeriodOfAvailability	Identifies the last year of availability under law that an account (annual and multiyear) may incur new obligations.
FederalEmployerIdentificationNumber	A number assigned to businesses by the IRS and used by DHHS for tracking child support payments.
IndefiniteDeliveryVehicleAgencyIdentifier	This is a code for an agency, but it does not necessarily represent the agency that issued the contract. Instead, it serves as part of the unique identification for Federal Procurement Data System IDV records. For awards records, it partially identifies a linked IDV record.
IndefiniteDeliveryVehicleProcurementInstrumentIdentifier	When reporting orders under Indefinite Delivery Vehicles (IDV) such as a GWAC, IDC, FSS, BOA, or BPA, report the Procurement Instrument Identifier (Contract Number or Agreement Number) of the IDV. For the initial load of a BPA under a FSS, this is the FSS contract number. Note: BOAs and BPAs are with industry and not with other Federal Agencies.
InputSystem	Identifies the sending trading partner.
IsCredit	Indicates if the item is a debit or credit, for example, a value of '1' would mean that it is a 'credit'. If the attribute is not populated, then the default value is understood to be '0'.
IsSpecialHandling	Requires agency / Treasury collaboration prior to use. Used for manual handling of checks such as the designated agent.
IsTOP_Offset	Indicates the payment eligibility of the payment offset
MainAccountCode	Identifies the type and purpose of the fund.

Field Name	Definition
PayeeName	Contains the full name of a payee. The name of the party whether individual or organization.
PayeeName_Additional	Contains the full name of an additional payee. The name of the additional party whether individual or organization.
PayeeAddressLine_1-4	The mailing address of the payee. Address lines left blank will not be printed.
PayeeIdentifier	The payee's Taxpayer Identification Number (TIN), Vendor ID, SSN, or other valid Payee ID.
PayeeIdentifier_Additional	The additional party's Taxpayer Identification Number (TIN), Vendor ID, SSN, or other valid ID.
PayeeStreetAddress	Address of the payee for mailing TOP offset letter, if needed, for ACH payments. For IAT payments, this field is required.
PayerMechanism	Identifies the payment medium for the transaction.
PaymentIdentifier	Used as a unique identifier for each payment to relate the records appropriately. Also used for matched letters.
PaymentIdentificationLine_1-14	Content to be printed on check stubs.
Payment Recipient TIN indicator	Indicates whether the TIN is an SSN or EIN.
PaymentTypeCode	The type of payment as defined in <a href="#">Appendix E</a> .
PostalCode	A code of letters and/or digits added to an address line. (Zip code)
PostalCodeExtension	4-digit extension of postal code.
PostNetBarcodeDeliveryPoint	Part of the PostNet barcode that is applied to the check for obtaining postage discounts.
PostNetBarcodeCheckDigit	Part of the PostNet barcode that is applied to the check for obtaining postage discounts.
ProcurementInstrumentIdentifier	The unique identifier for each contract, agreement or order associated with the payment.
ProcurementAgencyIdentifier	Code for a governmental agency, but it does not necessarily represent the agency that issued the contract. Instead, it serves only as part of the unique identification for Federal Procurement Data System awards records.
Reconcilement	Free-form field for agency's use in reconciling the payment using PACER. Data in this field is passed to PACER when formatted correctly. Contact Treasury for additional information.
Record Code	A set record identifier used to specify the type of record in the file.
RoutingNumber	The routing number is used synonymously as ABA routing number and routing transit number. The routing number consists of 9 digits, for example XXXXYYYYC where XXXX is Federal Reserve Routing Symbol,

Field Name	Definition
	YYYY is ABA Institution Identifier, and C is the Check Digit. The first two digits of the nine digit routing number must be in the ranges 00 through 12, 21 through 32, 61 through 72, or 80. The digits are assigned as follows: 00 is used by the United States Government; 01 through 12 are the normal routing numbers; 21 through 32 were assigned only to thrift institutions (e.g. credit unions and savings banks) through 1985, currently are still used by the thrift institutions, or their successors; 61 through 72 are used for electronic transactions; 80 is used for traveler's checks. The first two digits correspond to the 12 Federal Reserve Banks.
ScheduleAmount	The total dollar amount associated with the schedule.
ScheduleCount	Total number of payments for each schedule.
ScheduleNumber	A number assigned by the agency to identify a group of payments.
Standard Payment Request Version Number	The version of the PAM Standard Payment Request that this file is programmed against.
StandardEntryClassCode	<p>A three digit code defined by NACHA to characterize the nature of the ACH transaction.</p> <ul style="list-style-type: none"> <li>• PPD (Prearranged Payment and Deposit Entry) is an entry initiated by an organization pursuant to a standing or a single entry authorization from a receiver to effect a transfer of funds to impact a consumer account of the receiver.</li> <li>• CCD (Cash Concentration or Disbursement entry) is an entry initiated by an organization to affect a transfer of funds to impact the account of that organization or another organization.</li> <li>• IAT (International ACH Transaction) is a payment that involves a financial agency's office that is not located in the territorial jurisdiction of the United States.</li> <li>• CTX (Corporate Trade Exchange) is a corporate format which allows for up to 9,999 addenda records allowing full and complete remittance information to be transmitted with a single payment.</li> </ul>
StateCodeText	The US state code as managed by the USPS (United States Postal Service).
StateName	The foreign state, province or territory name.
StubLine_1 (through 14)	Agency data to be printed on the stub. Agencies interested in using this service should contact Treasury.
Sub-accountCode	Identifies an available receipt or other Treasury-defined subdivision of the main account.
Sub-levelPrefixCode	When populated, represents a programmatic breakdown of the account for Treasury publication purposes.
TotalAmount_Payments	Total amount of the payment request file. Used to verify the integrity of the file.
TotalCount_Payments	Total number of payments in the file. Used to verify the integrity of the file.
TotalCount_Records	Total number of records in the file. Used to verify the integrity of the file.

Field Name	Definition
USPSIntelligentMailBarcode	Field used for all intelligent barcode data elements. An agency must work with Treasury and the US Postal Service to arrange for this service.

### ***3.5 Appendix E - PaymentTypeCode Values***

Consult Treasury to determine **PaymentTypeCode** and TOP offset eligibility.

<b>PaymentTypeCode</b>	<b>Notes</b>
Allotment	
Annuity	
ChildSupport	
Daily Benefit	
Education	Reserved for use by VA
Fee	
Insurance	Reserved for use by VA
Miscellaneous	
Monthly Benefit	
Refund	
Salary	
Thrift	
Travel	
Vendor	